

IP DOME 2 MP WITH PoE



FEATURES

- Full HD resolution Sony® CMOS sensor
- IR illumination up to 30 meters
- 3,6 mm fixed lens
- AWB, AGC, BLC, HLC, Digital WDR, 2D/3D-DNR, defog
- Mirror, motion detection, privacy mask
- IP66
- 3AXIS: Installable on wall and ceiling
- PoE supported
- Compatible with DNS DEMES service

SOFTWARE & APPS

- Hyuviewer (Android & iOS)
- HYU CMS Client software
- P2P Cloud service: mycloud.hyundai-security.es



ACCESSORIES


HYU-24: Base tube

HYU-30: Wall bracket

HYU-31: Ceiling bracket



Dimensions



CAMERA

Image sensor	2.1MP 1/2.8 Sony® CMOS
Effective pixel	1984(H) x 1105(V)
Frames per second	PAL/NTSC: 25/30 fps @1080P
Electronic shutter	Auto, 1/25s ~ 1/50.000s, FLK, 1 ~ 30X
IR illumination	36 leds Ø5 mm: 20 ~ 30 meters
Minimum illumination	0 lux IR ON

LENS

Lens	3,6 mm
------	--------

FUNCTIONS

Day/night	Auto (ICR), Color, B/W, Ext
OSD menu	Supported
White balance	AWB, ATW, indoor, outdoor, manual
Gain control	AGC
Backlight compensation	BLC, HLC, Digital WDR
Noise reduction	2D/3D-DNR
Defog	Supported
Mirror	Supported
Motion detection	Supported
Privacy mask	Supported

ELECTRIC & ENVIRONMENT

Power supply	12V DC (±10%) /650 mA
Consumption	<8W
PoE	Supported
Working temperature	-20°C ~ +60°C
RH	10% ~ 90% RH
Protection degree	IP66

PHYSICAL FEATURES

Dimensions	Ø119 x 98 mm
------------	--------------