

WiFi IP BULLET CAMERA, 2MP WITH POE



FEATURES

- Full HD resolution with CMOS sensor
- Video compression H.264/MJPEG
- IR illumination up to 30 meters
- 3.6 mm fixed lens
- OSD menu, AGC, BLC, Digital WDR, 3D-DNR
- Mirror, motion detection, privacy mask
- Tripwire and intrusion detection
- IP67
- 3 AXIS bracket with wiring holes
- Built in WiFi, PoE supported
- Plug&Play connection with NEXTGEN NVR
- Compatible with DDNS DEMES

SOFTWARE AND APPS

- HYUVMS and HYUCONNECT for Android and iOS
- HYU VMS client software
- Cloud P2P service: hyucloud.hyundai-security.es




ACCESSORIES



HYU-248
Tube base

DIMENSIONS



CAMERA

Image sensor	1/2.8" CMOS, 2MP
Effective pixels	1920(H) x 1080(V)
Resolution	Stream 1 1080P, 1,3MP, 720P (25/30 fps)
	Stream 2 704x576, 640x480, 352x288, 320x240 (25 fps)
Electronic shutter	1/3s ~ 1/100.000s
IR illumination	20 ~ 30 meters
Minimum illumination	0,01 lux F1.2 (AGC On) / 0,028 lux F2.0 (AGC On) / 0 lux IR ON

LENS

Lens	3,6 mm
Viewing angle	85°

FUNCTIONS

Day/night	Removable mechanical filter (automatic switch)
OSD menu	Supported
Gain control	AGC
Backlight compensation	BLC, Digital WDR
Noise reduction	3D-DNR
Mirror	Supported
ROI	Supported
Privacy mask	Supported

INTELLIGENT ANALYSIS

Intelligent detection	Tripwire detection, intrusion detection, motion detection, dynamic analysis
-----------------------	---

AUXILIARY INTERFACE

Memory card slot	MicroSD/SDHC/SDXC card slot (up to 128 GB)
------------------	--

WiFi

WiFi standard	IEEE802.11b/g/n
Range	Up to 15 meters

ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±10%)
Consumption	Max. 5,8W
PoE	Supported
Working temperature	-30°C ~ +60°C
RH	≤95% (without condensation)
Protection	IP67

PHYSICAL FEATURES

Case	Metal
Dimensions	70 x 157 x 62 mm
Weight	500 g